

SAFETY DATA SHEET

Product: Prolong 95053 "A" Page 1 of 3 Date of Issue: January 2008

Hazardous according to criteria of Worksafe Australia

1 PRODUCT & COMPANY UNDERTAKING IDENTIFICATION

Product Name: Prolong 95053 "A" Aluminium Liquid
Major Recommended Use: Metal repair composite when mixed with "B".
Company: Peerless Industrial Systems Pty Ltd
ABN: 14 097 615 391
Address: PO Box 407 Cloverdale WA 6985 AUSTRALIA
Telephone Number: 61 (08) 9477 3788
Fax Number: 61 (08) 9477 3766
Email: service@peerlessindustrialsystems.com

2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Proportion	Classification
Epoxy Resin	25068-38-6	<40%	R36/38 R43 R51/53
Ingredients determined not to be hazardous		to 100%	
Description Resin			

3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact (R43). Irritating to eyes and skin (R36/38).

SUSDP: 5

ADG CLASS: Not regulated

Signs and Symptoms of Exposure (Acute effects):

Swallowed: Ingestion may cause: headache, nausea, vomiting.

Eye: Contact with eyes can cause mild irritation and discomfort, and may cause conjunctivitis and corneal edema when absorbed into the tissue of the eye from the atmosphere. Corneal edema may give rise to a perception of blue haze or fog around lights. This effect is transient and has no known residual effect.

Skin: Contact with skin can cause irritation, redness and discomfort which is transient. Prolonged and repeated contact may result in skin sensitisation.

Inhaled: Risk of exposure to hazardous concentrations of vapour is unlikely.

Chronic: Repeated and/or prolonged exposures may result in: adverse skin effects (defatting, rash or allergic reaction/sensitisation), adverse eye effects (conjunctivitis).

4 FIRST AID MEASURES

Swallowed: Administer 3-4 glasses of milk or water and seek medical advice immediately.

Eye: Immediately flush with plenty of water for at least 15 minutes. Retract eyelids often. Seek medical advice.

Skin: Remove any contaminated clothing and product. Wash skin thoroughly with mild soap/water. Flush affected areas with water for 15 minutes. Seek medical advice if ill effect or irritation develops.

Inhaled: Move patient to fresh air. Give oxygen or artificial respiration if breathing has stopped or is laboured. Seek medical advice.

First Aid Facilities: Product is supplied and used as a 2 part polymer system designed to cure to a hard solid.

Exposure to either part may not be able to be determined with any surety, and data on health effects during cure are not available. It is therefore suggested that the exposure be assumed to be to mixed, curing product, and appropriate consideration be given to seeking immediate medical advice.

Advice to Doctor: As per "First Aid Facilities", doubt may exist as to whether the particular substance requiring treatment is "A" or "B", or if it is a mixture undergoing cure to a hard plastic. The health hazard information relates to the greatest known risk. Remove stomach contents by gastric suction or induce vomiting as appropriate. Ingredients may be corrosive to some body tissues, therefore secondary treatment considerations will be required.

5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Ignition will give rise to a Class B fire. In case of large fire use: water spray, alcohol foam. In case of small fire use: carbon dioxide (CO₂), dry chemical, dry sand or limestone.

Special Exposure Hazards (fire fighting): May generate toxic, irritating or flammable combustion products. Sudden reaction with fire may result if product is mixed with an oxidising agent. May generate carbon monoxide gas. Personnel in vicinity and downwind should be evacuated.

Special Fire Fighting Procedures: Firefighters should wear butyl rubber boots, gloves, and body suit and a self contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Precautions: Wear protective clothing, boots, gloves, and eye protection.

Methods for Cleaning Up: If recovery is not feasible, admix with dry soil, sand or non reactive absorbent and place in an appropriate chemical waste container. Transfer to containers by suction, preparatory for later disposal. Flush area with water spray. Clean up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. For large spills, recover spilled material with vacuum truck.

7 HANDLING & STORAGE

Handling: Avoid contact with skin or eyes. When handling, do not eat, drink, or smoke.

Storage: Keep away from oxidisers. Keep in cool, dry ventilated storage and in closed containers.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: Not established

Engineering Controls: Conventional airflow is generally considered to be acceptable. In confined areas, exhaust fans should be utilised in accordance with good working practices.

Hand Protection: Neoprene rubber, Impermeable gloves, Cuffed butyl rubber, Nitrile rubber, or PVC gloves are suitable.

Eye Protection: Splash proof eye goggles.

Skin Protection: Long sleeved clothing.

Flammability: Non flammable

9 PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Thick Liquid
Smell:	None discernible
pH:	7
Boiling Point (@760mm Hg):	> 230°C
Melting Point:	No data
Flashpoint (°C):	> 200°C Closed Cup
Flammability:	Not applicable
Ignition Temperature:	No data
Explosive Properties:	No data
Explosive Limits:	No data
Oxidising Properties:	No data
Vapour Pressure (mm Hg):	> 3.9 @ 20°C
Vapour Density:	No data
Solubility in Water:	Insoluble
Solubility in Ethanol:	Insoluble
Solubility in n-Octanol:	No data
Partition Coefficient n-Octanol/Water	No data
Specific Gravity:	2.2
Per cent Volatiles:	< 0.5%
Volatile Organic Compounds:	< 0.5%

10 STABILITY & REACTIVITY

Conditions to Avoid: Not applicable.

Incompatibility (Materials to Avoid): Oxidising agents, Sodium or Calcium Hypochlorite. Reaction with peroxides may result in violent decomposition.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide in a fire. Irritating and toxic fumes at elevated temperatures.

Hazardous Transformation Products: Will not occur.

11 TOXICOLOGICAL INFORMATION

Acute Oral Toxicity (LD50, rat): No data.

Acute Dermal Toxicity (LD50, rabbit): No data.

Acute Inhalation Toxicity (LC50, rat): No data.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No data.

Environmental Fate: No data.

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local and national regulations. Wear protective clothing during disposal operations. If disposal by a waste contractor, make sure that he has sufficient information and that waste containers are properly labelled.

Where disposal of surplus stock is required, Cure as per use directions to enable possible disposal by conventional waste disposal techniques

14 TRANSPORT INFORMATION

ADR/RID Shipping Data: Not regulated.

IMO Shipping Data: Not regulated.

ICAO/IATA Shipping Data: Not regulated.

15 REGULATORY INFORMATION

EEC Symbol: Irritant (Xi)

EEC Council Directives relating to the classification, packaging and labelling of dangerous substances and preparations Risk (R) and Safety (S) phrases: May cause sensitisation by skin contact (R43). Irritating to eyes and skin (R36/38).

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26). Wear suitable protective clothing and gloves (S36/37).

16 OTHER INFORMATION

This Safety Data Sheet has been written to comply with Directives 93/112/EEC and 88/379/EEC to comply with KEMI General Recommendations 1998:1

Intended Use: Epoxy Resin for Curing Agent

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material